



Picking to packing

Crop care

Harvest & transportation

Crop protection

Handling systems

HortiKey

Components

Service maintenance



MetoSWT spray robot

We offer you:

- No unnecessary hoses on the path
- Uniform spray quality
- User-friendly control
- Suitable for intensive use

The MetoSWT has been specially developed for local spraying without any hoses laying over the concrete path. This keeps the main aisle free for other activities. You can use the touchscreen for spray settings, but also for displaying the most important measurement values. The spray robot is equipped with two spray booms, which can be separately controlled. One spray boom directed at the crop and the other on the gable end wall. This setup gives your crops optimal protection. The MetoSWT is fitted with a 300 litre tank. The innovative undercarriage ensures a constant weight distribution on the pipe rail system.

Berg Hortimotive

Burg. Crezeelaan 42a | 2678 KZ De Lier | Nederland
T +31 (0)174 - 51 77 00 | sales@berghortimotive.nl

www.berghortimotive.nl

MetoSWT spray robot



Easy to fill tank and clear indication of the amount of liquid



The touchscreen control can be set intuitively for pressure, speed, start and stop for local spraying and stop distance for end of path



The stainless steel sheeting provides good protection against the different spraying agents and a long service life



The innovative spray boom setting provides fast and simple height adjustment

Technical specifications MetoSWT spray robot		
Length	(cm)	235
Width	(cm)	HOH + 27
Height	(cm)	140
Capacity	(l)	300
Motor power	(kW)	0.45
Weight (empty)	(kg)	595
Max. speed	(m/min)	110
Batteries	(V/Ah)	24/360
Rail width	(cm)	42 - 60
Pipe size	(mm)	45 & 51
Touchscreen languages		NL, EN



Berg Hortimotive

Burg. Crezeelaan 42a | 2678 KZ De Lier | Nederland
T +31 (0)174 - 51 77 00 | sales@berghortimotive.nl

www.berghortimotive.nl